

Two Conductor Power Cables

0,6/1kV Armoured & Sheated



DESIGN

| | |
|--------------------|--|
| Conductor | Soft annealed stranded bare or tinned copper per IEEE1580 |
| Separation Tape | Polyester tape if required |
| Insulation | Type P flame retardant cross-linked polyolefin compound, X110 meeting the requirements for IEEE 1580 Type P and UL1309 |
| Jacket | CPE, Flame retardant, oil abrasion, chemical resistant thermosetting compound as required IEEE1580 |
| Armor | Basket weave bronze wire armour per IEEE1580 and UL1309/ CSA C22.2 No.245. Tinned copper wire available by request |
| Sheath | CPE, Flame retardant, oil abrasion, chemical and sunlight resistant thermosetting compound as required IEEE1580 |
| Outer Sheath Color | Black |
| Reference Standard | IEEE 1580, UL 1309, CSA C22.2 No.245 |
| Temperature Rating | Untel 125°C / UL CSA 110°C / IEEE 100°C |
| Flame Retardant | IEEE 1202 & IEC 60332-3 cat. A |
| Cold Bend/Impact | -40°C / -35°C (CSA 22.2 No.03) |

These cables are intended for use as control and power cables aboard ship and on off-shore oil rigs. The cables are constructed in accordance with the recommended practice for marine cable for use on fixed or floating facilities, IEEE 1580. Excellent resistance to oil, abrasion petrochem fluids, moisture salty water and sunlight.

Physical Characteristics

| Size AWG | Diameter (inches) | Weight (lbs/Mft) | Ampacity 110°C | Ampacity 100°C |
|----------|-------------------|------------------|----------------|----------------|
| 16 | 0,540 | 202 | 21 | 19 |
| 14 | 0,561 | 230 | 33 | 31 |
| 12 | 0,601 | 263 | 41 | 40 |
| 10 | 0,641 | 307 | 52 | 49 |
| 8 | 0,781 | 416 | 68 | 64 |
| 6 | 0,903 | 559 | 90 | 85 |
| 4 | 1,110 | 835 | 115 | 110 |
| 1/0 | 0,466 | 1562 | 208 | 199 |
| 4/0 | 1,878 | 2680 | 323 | 307 |